

HENKOVAC THERMOFORMERS:

WORLDCLASS THERMOFORMER FOR FLEXIBLE AND RIGID FILM

- > **Film widths: 285 - 320 - 355 - 420 mm**
- > **Strokes: 240 - 270 - 300 mm**

The range of thermoformers has been designed to satisfy the requirements of small to medium size processing operations that require the best value for their money in performance, hygiene, quality, reliability, serviceability and durability. The intuitive, user friendly control system make programming easy, provides relevant management information and safeguards proper operation. All parts are very accessible for easy service and cleaning. The uncompromising choice of quality materials and design makes us proud to be able to offer this range of thermoformers.



Standard

- > Display prepared for remote connection and control through Ethernet; for example for software updates
- > Synchronisation for peripheral devices such as a labeler, printer, filler or loading robot
- > Control cabinet heating to prevent condensation on electrical circuits

Optional

	1	2	3
> Length	3000		
> Pump	63 m ³	100 m ³	160 m ³
> Gas	Inert	Oxygen	
> Exit Conveyor	Rollers	Powered chain belt	
> Film	Print sensor	Euro hole	

SPECIFICATIONS THERMOFORMER

	MACHINE LENGTH	MACHINE WIDTH	MACHINE HEIGHT	VOLTAGE*	POWER CONSUMPTION	AIR	WATER
TH 285/320/355	3500	727	1708	400V-3-50Hz	7,5 kw	6 bar 200 Ltr/min	2,1Ltr/min 1,5 bar
TH 420	3500	792	1708	400V-3-50 Hz	7,5 kw	6 bar 200 Ltr/min	2,1Ltr/min 1,5 bar
	FILM THICKNESS	MAX DEPTH					
FLEXIBLE FILM	< 300 μ	95					
RIGID FILM	Ca. 300-400 μ	60					
SKIN PACK	x	20					

Dimensions in mm *Machines can be supplied with all worldwide voltages applicable

MODELS THERMOFORMERS

MODEL	WIDTH	STROKE	LOADING AREA
TH 285-240	285	240	1400
TH 285-270	285	270	1300
TH 285-300	285	300	1100
TH 320-240	320	240	1400
TH 320-270	320	270	1300
TH 320-300	320	300	1100
TH 355-240	355	240	1400
TH 355-270	355	270	1300
TH 355-300	355	300	1100
TH 420-240	420	240	1400
TH 420-270	420	270	1300
TH 420-300	420	300	1100

Dimensions in mm